

Isolate
10/64 **5Y4GT**


Full-Wave Vacuum Rectifier

The 5Y4GT is the same as the 5Y4GA except for the following items:

Mechanical:

Operating Position. Vertical, base down or up, or
Horizontal with pins 2 and 3 in vertical plane
Maximum Overall Length. 3-3/8"
Maximum Seated Length. 2-13/16"
Maximum Diameter. 1-9/32"
Dimensional Outline. See General Section
Bulb. T9
Base. Intermediate-Shell Octal 6-Pin,
Arrangement 1 (JEDEC Group 1, No.B6-8), or
Short Intermediate-Shell Octal 6-Pin
with External Barriers, Arrangement 1
(JEDEC Group 1, No.B6-60)
Basing Designation for BOTTOM VIEW. 5Q

Pin 1 - No Connection
Pin 2 - No Connection



Pin 3 - Plate No.2
Pin 5 - Plate No.1
Pin 7 - Filament
Pin 8 - Filament

5Z3


Full-Wave Vacuum Rectifier

The 5Z3 is the same as the 5U4G except for the following items:

Mechanical:

Operating Position. Vertical, base down or up, or
Horizontal with pins 1 and 4 in horizontal plane
Maximum Overall Length. 5-3/8"
Base. Medium-Shell Small 4-Pin (JEDEC No.A4-9)
Basing Designation for BOTTOM VIEW. 4C

Pin 1 - Filament
Pin 2 - Plate No.2



Pin 3 - Plate No.1
Pin 4 - Filament



RADIO CORPORATION OF AMERICA
Electron Tube Division
Harrison, N. J.

DATA
7-61